


Rail Mounted Terminal Blocks : Polyamide Range Of Terminals : Thermocouple Terminal : KUT4NTCE



Type of Connection	MS Screw Clamp
Insulating Material	Polyamide 66
Terminal Pitch	12 mm (0.47 Inch)
Terminal Width	41.4 mm (1.61 Inch)
Terminal Height	51 mm (1.99 Inch)
Rated Cross Section	4 sq mm
Wire Stripping Length	12 mm
Screw Size	M3



Connection Possibility


Stranded wire	Max : 4 sq mm	Min : 0.5 sq mm
Solid wire	Max : 4 sq mm	Min : 0.5 sq mm

Ratings	IEC
Voltage	400 V
Current	5 A
Conductor Size	4 sq mm
Tightening Torque	0.5 Nm

Terminal Accessories

End Plate	KPXN
Partition Plate With Foot	KNBF 2.5/10
Protection Cover	PCK3
End Clamp	SCUN, SCUSL, SCUDD, SCKN, DCKN
Marking Label	LABEL KN5.5
Group Marking Carrier	SCKNMLH, SCUNMLH, DCKNMLH
Terminal Colours	GREY, KHAKHI, RED, YELLOW, BLUE, BLACK, GREEN
Mounting Channel	CHS10, CHK10, CHS3, CHS5, CHK5, CHK3, CHKS3, CHKS5, CHKS10, CHKDS10, CHKD10

Rail Mounted Terminal Blocks : Polyamide Range Of Terminals : Thermocouple Terminal : KUT4NTCJ



Type of Connection	MS Screw Clamp
Insulating Material	Polyamide 66
Terminal Pitch	12 mm (0.47 Inch)
Terminal Width	41.5 mm (1.62 Inch)
Terminal Height	51 mm (1.99 Inch)
Rated Cross Section	4 sq mm
Wire Stripping Length	12 mm
Screw Size	M3



Connection Possibility


Stranded wire	Max : 4 sq mm	Min : 0.5 sq mm
Solid wire	Max : 4 sq mm	Min : 0.5 sq mm

Ratings	IEC
Voltage	400 V
Current	5 A
Conductor Size	4 sq mm
Tightening Torque	0.5 Nm

Terminal Accessories

End Plate	KPXN
Partition Plate With Foot	KNBF 2.5/10
Protection Cover	PCK3
End Clamp	SCUN, SCUSL, SCUDD, SCKN, DCKN
Marking Label	LABEL KN5.5
Group Marking Carrier	SCKNMLH, SCUNMLH, DCKNMLH
Terminal Colours	GREY, KHAKHI, RED, YELLOW, BLUE, BLACK, GREEN
Mounting Channel	CHS10, CHK10, CHS3, CHS5, CHK5, CHK3, CHKS3, CHKS5, CHKS10, CHKDS10, CHKD10

Rail Mounted Terminal Blocks : Polyamide Range Of Terminals : Thermocouple Terminal : KUT4NTCK



Type of Connection	MS Screw Clamp
Insulating Material	Polyamide 66
Terminal Pitch	12 mm (0.47 Inch)
Terminal Width	41.5 mm (1.62 Inch)
Terminal Height	51 mm (1.99 Inch)
Rated Cross Section	4 sq mm
Wire Stripping Length	12 mm
Screw Size	M3



Connection Possibility


Stranded wire	Max : 4 sq mm	Min : 0.5 sq mm
Solid wire	Max : 4 sq mm	Min : 0.5 sq mm

Ratings	IEC
Voltage	400 V
Current	5 A
Conductor Size	4 sq mm
Tightening Torque	0.5 Nm

Terminal Accessories

End Plate	KPXN
Partition Plate With Foot	KNBF 2.5/10
Protection Cover	PCK3
End Clamp	SCUN, SCUSL, SCUDD, SCKN, DCKN
Marking Label	LABEL KN5.5
Group Marking Carrier	SCKNMLH, SCUNMLH, DCKNMLH
Terminal Colours	GREY, KHAKHI, RED, YELLOW, BLUE, BLACK, GREEN
Mounting Channel	CHS10, CHK10, CHS3, CHS5, CHK5, CHK3, CHKS3, CHKS5, CHKS10, CHKDS10, CHKD10

Rail Mounted Terminal Blocks : Polyamide Range Of Terminals : Thermocouple Terminal : KUT4NTCT



Type of Connection	MS Screw Clamp
Insulating Material	Polyamide 66
Terminal Pitch	12 mm (0.47 Inch)
Terminal Width	41.5 mm (1.62 Inch)
Terminal Height	51 mm (1.99 Inch)
Rated Cross Section	4 sq mm
Wire Stripping Length	12 mm
Screw Size	M3



Connection Possibility

Stranded wire	Max : 4 sq mm	Min : 0.5 sq mm
Solid wire	Max : 4 sq mm	Min : 0.5 sq mm

Ratings	IEC
Voltage	400 V
Current	5 A
Conductor Size	4 sq mm
Tightening Torque	0.5 Nm

Terminal Accessories

End Plate	KPXN
Partition Plate With Foot	KNBF 2.5/10
Protection Cover	PCK3
End Clamp	SCUN, SCUSL, SCUDD, SCKN, DCKN
Marking Label	LABEL KN5.5
Group Marking Carrier	SCKNMLH, SCUNMLH, DCKNMLH
Terminal Colours	GREY, KHAKHI, RED, YELLOW, BLUE, BLACK, GREEN
Mounting Channel	CHS10, CHK10, CHS3, CHS5, CHK5, CHK3, CHKS3, CHKS5, CHKS10, CHKDS10, CHKD10